RICOH

Advanced & Versatile Business Communications Solution



FAX4430NF

Efficient Document Distribution for Mid to Large Workgroups



The basis for smooth running office communication? An all-round document workflow solution that is highly productive, cost effective and easy to use. With the FAX4430NF, Ricoh introduces a superbly equipped workgroup solution, designed to fully meet your fax demands. As many offices rely on their fax solution for their every day communications, Ricoh now offers the extra tool for efficient document distribution. With the FAX4430NF, an optimised document workflow is within everybody's reach.

- Fast 2-second transmission
- · 200 speed dials
- 70-sheet ADF
- Internet and IP faxing
- Duplex faxing & colour scanning
- · Advanced security features

Faxing Made Cost Effective

The FAX4430NF offers fast document distribution without the usual high price tag. The system's 33.6 Kbps modem speed provides low cost transmission while the separate toner and developer keep supply costs at an absolute minimum.



Optimum Performance & Ease of Use

- STTcanning is done in a mere 1.3 seconds.
- · A continuous output speed of 15 ppm is guaranteed.
- · 10 user function keys, 90 quick dial and 200 speed dial keys for extra convenience.
- It takes only seconds to replace toner or replenish paper.

Afraid you might not receive important messages because your fax device runs out of paper? With its standard 350-sheet paper capacity you can easily leave the FAX4430NF unattended. Add the two 500-sheet optional paper feed units and eliminate the need for frequent paper refills! Moreover, the FAX4430NF guarantees all incoming information is safeguarded as 1,280 A4 pages can be stored in the system's 16 MB memory.



.....

GB

250 sheets

500 sheets

500 sheets

- - Highly user friendly
- · Virtually eliminates the costs of sending (long distance) faxes

With the IP fax function, costless long distance faxing to any office connected directly to the same network becomes a reality.

Advanced Business Communications

- · Save time and improve image quality by transmitting fax messages directly from your PC (LAN fax).
- Save time and costs by sending faxes in e-mail format to other fax devices or e-mail addresses (Internet fax).
- Send colour documents in TIFF, JPEG or PDF format as e-mail attachments with the combination of 'scan to e-mail' and 'colour scanning'.

Bypass tray: 100 sheets

Environmentally Friendly Faxing

Like all Ricoh products, the FAX4430NF reflects Ricoh's commitment to the environment through its low power consumption and zero waste · less than 6 W power consumption in energy saver mode · easily recyclable parts & long unit life

Benefit from IP Faxing

- The IP fax functionality transmits fax data over the IP/VoIP network. Using the IP address instead of the fax number to specify the destination machine, IP faxing offers you a variety of benefits:
- Extremely fast transmission speed
- · Easy network connectivity
- Improved fax quality
- · Reduced chance of errors; ideal for sending legal documents





Excellent Output Quality

The FAX4430NF perfectly recreates received documents, printing clear images and crisp text at a fine 400 dpi resolution. It also smoothes the rough edges of curved and oblique lines regardless of the type of machine that sent the original. Even subtle gradations and fine textures of photographic images and illustrations are reproduced in excellent quality.



Ensuring your Peace of Mind

The FAX4430NF makes sure your fax workflow is secure and trouble free. Before operating the machine, each user is asked to put in a personalised authorisation code, avoiding unrestricted use. The memory lock functionality stores incoming faxes into memory and only releases them after proper authentication. The IP fax function enables secure and reliable fax transmission of confidential data.





FAX4430NF

Specifications

()

GENERAL

SCAN 1	Γ

SCAN TO E-MAIL (COLOUR²)

Туре:	Desktop type transceiver
Circuit:	PSTN, PABX
Compatibility:	ITU-T (T.30) group 3 machines
	ITU-T (T.37) Internet Fax
	ITU-T (T.38) IP Fax
Interface:	Network Port Ethernet 10 base-T/100 base-TX
LAN fax:	Yes
Network utility:	Web Status Monitor
Modem speed:	33.6 Kbps
Transmission speed:	2 seconds
Compression method:	MH, MR, MMR, JBIG
Quick dial:	90 numbers
Speed dial:	200 numbers
Paper input capacity:	Standard: 1 x 250-sheet paper tray
	100-sheet bypass tray
	Maximum: 1.350 sheets

Resolution:
Output formats:

Maximum 600 x 600 dpi TIFF/PDF/JPEG²

CONSUMABLES

- Toner hopper magazine (yield: 5,000 sheets)¹
- · Photo conductor unit (yield: 45,000 sheets)
- ADF maintenance kit

OTHER OPTIONS

- 2 x 500-sheet paper tray
- · G3 unit (for second fax number)
- Colour unit

70 sheets ADF capacity: 16 MB (1,280 pages)¹ Memory capacity: Memory backup: 12 hours A4 Document size: 1.3 seconds Scan speed: Dimensions $(W \times D \times H)$: 448 x 551 x 411 mm Weight: 23 kg 220 - 240 V, 50/60 Hz Power source: Power consumption (energy saver mode): Less than 6 W

¹ Based on ITU-T #1 chart.

² Optional.

For availability of models, optional apparatus and software, please consult your local Ricoh supplier.



ISO9001: 2000 certified ISO14001 certified

Ricoh has designed this product to meet EC ENERGY STAR guidelines for energy efficiency.

Ricoh believes in conserving the earth's precious natural resources. This brochure is printed on environmentally friendly paper: 50% recycled fibres, 50% chlorine free bleached pulp.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

Copyright © 2007 Ricoh Europe (Netherlands) B.V. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe (Netherlands) B.V.

RICOH EUROPE (NETHERLANDS) B.V. P.O. Box 114, 1180 AC Amstelveen, The Netherlands.

For more information, please contact:

Phone: +31 (0)20 54 74 111 Fax: +31 (0)20 54 74 222

www.ricoh-europe.com

RICOH